

SILICATE EX

Algae



HIGH

CAPACITY



SILICATE

REMOVAL



QUICK

ACTION



2.000 LTR

1.000 ML

Dosage

100 ml / 200 Ltr

Optimal value

Silicate

< 0,5 mg/l



Scan me for
more information



100 ml per 200 ltr seawater. Place the Silicate Ex in a fine filter bag. Wash the Silicate Ex well with flowing cold water to remove any dust. Place the filter bag on spot with good water flow. When the silicate level has dropped to the desired level, remove the Silicate Ex for future use.



100 ml par 200 litres d'eau de mer. Placez le Silicate Ex dans un sac filtrant fin. Lavez bien le Silicate Ex avec de l'eau froide pour éliminer toute trace de poussière. Placez le sac filtrant à un endroit possédant un bon débit d'eau. Lorsque le niveau de silicate a atteint le niveau souhaité, retirez le Silicate Ex pour une utilisation ultérieure.



100 ml pro 200 Liter Meerwasser. Legen Sie das Silicate Ex in ein feines Filternetz. Waschen Sie das Silicate Ex unter fließendem kaltem Wasser gründlich ab, um Staub zu entfernen. Positionieren Sie das Filternetz so, dass das Wasser ordnungsgemäß durch das Filtermaterial fließt.



100 ml per 200 ltr zeewater. Plaats de Silicate Ex in een fijn filternet. Was de Silicate Ex goed onder stromend koud water om eventueel stof te verwijderen. Plaats het filternet zo dat het water goed door het filtermateriaal stroomt.